


SIDE ELEVATION

END ELEVATION

TEMPORARY CONCRETE BARRIER

NOTES:

- INSERT PANEL TO BE SQUARE WELDED, HOT-DIPPED GALYANIZED STEEL WIRE-MESH 50x50x3 mm.
- . INSERT-PANEL TO BE SECURELY WELDED TO THE STEEL FRAME.
- STEEL FRAME TO BE HOT-DIPPED GALVANIZED PIPE 40mm DIAMETER AND 3.6mm WALL THICKNESS.
- . STEEL FRAME TO BE SECURELY WELDED ON ALL SIDES AND TREATED WITH GALVANIZED PAINT.
- . SHADE CLOTH IS TO BE DARK GREEN HEAVY DUTY 80% MONO-FILAMENT WITH 306gsm (GRAMS PER SQUARE METER)
- . SHADE CLOTHE IS TO BE SECURELY ATTACHED TO THE WELDED MESH INSERT PANEL WITH CABLE TIES.
- 7. FLASHING LAMPS OR BEACONS MAY BE ATTACHED TO THE WELDED MESH INSERT PANEL AS REQUIRED AND SHOULD BE INSTALLED AT APPROXIMATELY 1m FROM THE ROAD SURFACE,
- . CONCRETE BARRIER MOUNTED WORK-ZONE SCREENS ARE NOT TO BE USED IN 80 km/h AND ABOVE SPEED ENVIRONMENTS.
- 9. DIAGRAMS ARE NOT TO SCALE.
- 10. ALL DIMENSIONS QUOTED ARE IN MILLIMETERS.



هيئـــة الأشغــال العامـــة Public Works Authority

P.O.Box 22188 Tel.: (0974) 44950000 Fax.: (0974) 44950999 www.ashghal.gov.qa



PA PROJECTS AFFAIRS

Section 1 - General Part 14 - Temporary Works

TEMPORARY CONCRETE BARRIER MOUNTED **WORK-ZONE SCREENS**

Approved	:	Sheet No:	2	OF	2	
Date:	SEPTEMBER 2013	Scale:	N.	T.S.		
Drawing N	Number:					Revision:

SD 1-14-202