



NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE STATED.
2. ALL MATERIALS AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE CURRENT Q.C.S. UNLESS OTHERWISE AGREED WITH THE ENGINEER.
3. THE DRAWING SHOULD BE READ IN CONJUNCTION WITH DETAILS SHOWN ON STANDARD DRAWINGS.
4. VARIATION TO STANDARD DETAILS ARE PERMITTED TO MEET SITE SPECIFIC REQUIREMENTS SUBJECT TO ENGINEERS APPROVAL.
5. MINIMUM STRENGTH OF EPOXY MORTAR 30 N/mm².
6. CIRCULAR SEATING RINGS MAY BE USED ON FOUL SEWER MANHOLES WHERE GRP LINING IS REQUIRED.

| | | | |
|------|-----------|-------------------|-------|
| 3 | APR 19 | ISSUED FOR USE | |
| 2 | 01 MAR 19 | REVALIDATED ISSUE | |
| 1 | 23NOV15 | ISSUED FOR USE | |
| 0 | 15SEP13 | ISSUED FOR USE | |
| Rev. | Date | Revision Details | Appd. |

هيئة الأشغال العامة
Public Works Authority

P.O.Box: 22188
Tel.: 00974 44950000
Fax: 00974 44950999

قطر تستحق الأفضل
Qatar Deserves The Best
www.ashghal.gov.qa

QCS Section:
Section 8 - Drainage Works
Part 4 - Pipeline Installation

Drawing Title:

MANHOLE COVER SLAB &
SEATING RING DETAILS

| | |
|----------------------------|------------------|
| Approved: | Sheet No: 1 OF 1 |
| Date: APRIL 2019 | Scale: NTS |
| Drawing Number: SD 8-4-108 | Revision: 3 |